

SINCE 1978



OPTICS TECHNOLOGY

Manufacturer & Exporters of : LABORATORY TESTING INSTRUMENTS



An ISO 9001:2008 CERTIFIED
An ISO 10002:2004 CERTIFIED

CE Certified

High Temperature Hot Air Oven



High Temperature Hot Air Oven

Ovens are designed fabricated & tested to suit various applications in growing field of Medical Agricultural, Research Laboratories of Hospitals. Suitable to work on 220/230V AC supply.

CONSTRUCTION:- Double walled construction with inside Stainless Steel Chamber having 60-70mm glass wool insulation. Door is fitted with heavy chrome plated hinges & spring & roller type latch catch. Provided with adjustable steel wiremesh tray for better air circulation. **Available in models of outer construction being M.S. Body duly powder coated / Stainless steel SS304.**

TEMPERATURE RANGE : Ambient to 250°C ± 2° C . Temperature controlled by Hydraulic Type Capillary Thermostat and temperature reading will be on of "L" shape thermometer fitted at the front of the cabinet

HEATING : Heating elements are made from high grade (Kanthal ISI) Resistance wire. Heaters are fitted/wound along all sides & bottom. Complete with 2 pilot lamp cord & plug pin etc.

AVAILABLE SIZE		
SIZE INSIDE CHAMBER		
W X D X H	Ltrs.(App.)	No. Of Trays
300 x 300 x 300 mm (12" X 12"X 12")	28	1
355 x 355 x 355 mm (14" X 14"X 14")	45	1
450 x 450 x 450 mm (18" X 18"X 18")	95	2
450 x 450 x 600 mm (18" X 18"X 24")	128	2
600 x 600 x 600 mm (24" X 24"X 24")	227	3
600 x 600 x 900 mm (24" X 24"X 36")	340	3
OR ANY SPECIAL SIZE		

AVAILABLE MODELS:

- 1) Temperature controlled by digital temperature controller alongwith air circulating fan (± 1° C)
- 2) Temperature controlled by microprocessor based P.I.D. temperature controller alongwith air circulating fan (± 0.5° C)
- 3) Special Heavy Duty Air Circulating Fan System for continuous operation
- 4) Microprocessor Based PID Controller alongwith PC communication thru built-in RS-485 interface and printing option through software
- 5) Touch Screen Display (3.5") system & Pen Drive System alongwith data logging & for saving of data and communication to PC

TOUCH SCREEN (for Data Logging)

Touch Screen Display (3.5")

Menu driven settings for Controlling parameters / Setting

RTC accurate Date & Time Clock.

Pen Drive for saving of data for printing through PC communication

2/3, DSIDC, Community Works Centre, J-Block, Shakurpur, (Opp. Britannia Ind. Ltd.) Delhi-110034 (India)

Phone: 0091-11-27101383, 27184490, Fax: 0091-11-27108890

E-mail: info@opticstechnology.in, opticstechnology@gmail.com

Website: www.opticstechnology.in