

VACUUM TRAY DRYER RECTANGULAR CE



Vacuum Tray Dryer used in various industries under vacuum atmosphere to dry temperature-sensitive materials. It gives complete drying and vaporization of moisture of the product. Inside Chamber made of S.S. (304) & Outer Mild steel duly powder coated / S.S. Temperature controlled by Microprocessor based PID Controller, Temp. Stability $\pm 1^{\circ}$ C, Temperature Range 50°C to 130°C. It Fitted with Vacuum Release Valve, with Toughened Glass Door, Provided with S.S. Tray. Tray size **16" x 32"**.

With Suitable Vacuum Pump with Oil & Belt Motor System & With Vacuum Gauge, Moisture Trap & Non-Return Valve.

Model	No. of Tray
OT-VTD-138-MS/SS-A	4 No. S.S. Trays
OT-VTD-138-MS/SS-B	6 No. S.S. Trays
OT-VTD-138-MS/SS-C	8 No. S.S. Trays
OT-VTD-138-MS/SS-D	12 No. S.S. Trays
OT-VTD-138-MS/SS-E	24 No. S.S. Trays
OT-VTD-138-MS/SS-F	48 No. S.S. Trays

Optional:

- 1. Digital Vacuum Gauge
- 2. Microprocessor Based Touch Screen Display System with Data Logging

2/3, DSIDC, (Behind Fun Cinema) NSP, Pitampura, Delhi-110034 (INDIA) © 9811238150,9811238151,9811236960

E-mail: info@opticstechnology.in opticstechnology@gmail.com Website : www.opticstechnology.in