



AUTOMATIC AUTOCLAVE

CE

WITH TOUCH SCREEN SYSTEM



OT-AAUV-67 TS/SS



AUTOMATIC TOUCH SCREEN DISPLAY WITH DATA LOGGER

(Data Logging through PEN DRIVE)

- Microprocessor based touch screen display system with special features
- Automatic system with features like SETTING Sterilization Temp. Soak Time
- Purge On / Off set point Exhaust Set Point High Alarm Set Point ETC.
- Digital Pressure Indication with respect to temperature.
- Touch Screen (for Data Logging through PEN DRIVE)
- Pen Drive for saving of data for printing through PC communication
- Graphical presentation of Pressure with respect to Temperature
- Error indications (Both audible and visible) for Low water Level, Sensor Failure and High Temperature Cross Limit

WORKING CHAMBER SIZE

Model No.	Dia mm x Depth mm	Ltr. (Approx.)	Wattage
OT-AAUV-67/22/SS/MS	250 mm x 450 mm (10" x 18")	22	2 KW
OT-AAUV-67/35/SS/MS	300 mm x 500 mm (12" x 20")	35	2 KW
OT-AAUV-67/50/SS/MS	350 mm x 550 mm (14" x 22")	50	3 KW
OT-AAUV-67/75/SS/MS	400 mm x 600 mm (16" x 24")	75	4 KW
OT-AAUV-67/95/SS/MS	450 mm x 600 mm (18" x 24")	95	4 KW
OT-AAUV-67/145/SS/MS	400 mm x 750 mm (20" x 30")	145	6 KW
OT-AAUV-67/178/SS/MS	550 mm x 750 mm (22" x 30")	178	6 KW
OT-AAUV-67/210/SS/MS	550 mm x 900 mm (22" x 36")	210	9 KW
OT-AAUV-67/254/SS/MS	600 mm x 900 mm (24" x 36")	254	9 KW

Optional:

- Vacuum Breaker Valve
- Calibration Port
- Specially designed Lid locking system to make sure lid is locked properly
- Printing system with thermal printer
- 21 CFR Software