



AUTOMATIC AUTOCLAVE (VERTICAL) CE



Provided with microprocessor based LCD Display with Digital Temp. Controller Cum Timer system for setting temperature, purge time, exhaust time etc. Autoclave is controlled with the settings on this controller. The chamber is absolutely leak proof and can be operated at any Selected point in between 5 to 20 pounds per sq. Inch. It is provided with pressure gauge, pressure release valve, S. S. Basket, safety valve, water level indicator with cord, Plug & Pressure Control Switch. It is provided with Radial Locking System with Automatic Water Level cut off device for element.

WORKING CHAMBER SIZE

Model No.	Dia mm x Depth mm	Ltr. (Approx.)	Wattage
OT-AAUV-67/22/SS/MS	250 mm x 450 mm (10" x 18")	22	2 KW
OT-AAUV-67/35/SS/MS	300 mm x 500 mm (12" x 20")	35	2 KW
OT-AAUV-67/50/SS/MS	350 mm x 550 mm (14" x 22")	50	3 KW
OT-AAUV-67/75/SS/MS	400 mm x 600 mm (16" x 24")	75	4 KW
OT-AAUV-67/95/SS/MS	450 mm x 600 mm (18" x 24")	95	4 KW
OT-AAUV-67/145/SS/MS	400 mm x 750 mm (20" x 30")	145	6 KW
OT-AAUV-67/178/SS/MS	550 mm x 750 mm (22" x 30")	178	6 KW
OT-AAUV-67/210/SS/MS	550 mm x 900 mm (22" x 36")	210	9 KW
OT-AAUV-67/254/SS/MS	600 mm x 900 mm (24" x 36")	254	9 KW

Optional :

1. Vacuum Breaker Valve
2. Calibration Port
3. Safety Alarm
4. Specially designed Lid locking system to make sure lid is locked properly
5. Single channel data logger system (Only with Automatic Model)
6. Printing System with Thermal Printer
7. 21 CFR Software
8. Automatic System (Only for Normal Autoclave Vertical Model) OR
Microprocessor Based Automatic Touch Screen Display System with Data Logging

MOC : MS-Mild steel duly powder coated SS-stainless steel kindly select the one required in model number.

2/3, DSIDC, (Behind Fun Cinema) NSP, Pitampura, Delhi-110034 (INDIA)

☎ 9811238150, 9811238151, 9811236960

E-mail: info@opticstechnology.in,

opticstechnology@gmail.com,

Website : www.opticstechnology.in