



DOUBLE DECKER BACTERIOLOGICAL INCUBATOR



(LAB INCUBATOR)



OT-BI-58 DD-MS

DOUBLE DECKER
INCUBATOR

Double wall construction with inner Chamber Stainless Steel (S.S. 304) & Outer Body M.S. duly powder coated / Stainless Steel 304 Mounting One above the other with individual control box in the sides. Independent Doors. Independent controlling of temperature by 2 nos. microprocessor based PID controller. Removable SS wire mesh trays. The inner chamber is properly insulated with Glass Wool to prevent thermal losses. With Air Circulating Fan.

Temp. Range Amb. +5°C to 70°C

Model No.	Size W x D x H	Ltrs. (App.)	No. of Trays
OT-BI-DD/28 MS/SS	300 x 300 x 300 mm (12"x12"x12")	28	1
OT-BI-DD/45 MS/SS	355 x 355 x 355 mm (14"x14"x14")	45	1
OT-BI-DD/96 MS/SS	450 x 450 x 450 mm (18"x18"x18")	96	2
OT-BI-DD/128 MS/SS	450 x 450 x 600 mm (18"x18"x24")	128	2
OT-BI-DD/227 MS/SS	600 x 600 x 600 mm (24"x24"x24")	227	3

OR ANY NON STANDARD SIZE

Optional :

1. 2 Nos. special Heavy-Duty Air Circulating fan system for continous Non-stop working
2. 2 Nos. Microprocessor based Touch Screen with Pen Drive for data logging, Printing through PC communication & saving of data in PC
3. Online transfer of data without any Cable/Wire interference
4. 21 CFR Software (For Non Editable Data)